



Self-Contained Emergency Luminaires

2 x 3.0 W Power LED Weather Proof IP (65)

TEL - 30 LED (WP)



Specifications

- Model ➔ TEL-30 LED (WP)
- Light Source ➔ 2 x 3.0 watt High Output LED
- Mode ➔ Non-Maintained
- Weight ➔ ~ 1.5 Kg
- Battery ➔ 4 x 1.2V, 2.5AH High Temperature NI-CAD
- Charger ➔ Constant Current
- Mounting ➔ Surface mounting direct to wall
- Housing ➔ Injection moulded fire retardant ABS housing with die-casting aluminum lamphead
- Dimension (mm) ➔ 82mm(L) x 198mm (W) x 240mm (H)
- Monitoring ➔ Red LED indicating healthy supply and charging
- Compliance ➔ SIRIM MS 619-2-22:2005, MS IEC 60598-1:2012
Jabatan Bomba and Penyelamat Malaysia certified.
- Input Voltage ➔ 240 V +/- 10% 50/60 Hz
- Input Power ➔ ~3.8W
- Recharge Period ➔ 16 - 24 Hours
- Back Up Duration ➔ 3 Hours
- Battery Protection ➔ Low voltage cut-off to prevent over discharging.
- Degree of Protection ➔ IP - 65
- Operating Temperature ➔ 0 °C to 65 °C
- Ambient Temperature ➔ 40 °C
- Rated Lumen Output ➔ 400 lm - 312 lm

For further enquiries, please contact :-

PNE SYSTEMS SDN. BHD.

No.3, Jalan SS26/13,
Taman Mayang Jaya 47301, Petaling Jaya,
Selangor Darul Ehsan, Malaysia

Tel : 603-78037488 (Hunting)

Fax : 603-78038509

E-mail : sales@pnesys.com.my

Website : www.pnesys.com.my





TEL 30 LED WP INSTALLATION DIAGRAM

