



Self-Contained Emergency KELUAR Sign

PEX-215F-WP

LED Keluar Sign (IP 65)

PEX-215F-WP



Specifications

MODEL	➔ PEX-215F-WP
MODE	➔ Maintained
LIGHT SOURCE	➔ 18 nos SMD Super Bright LED
LAMP WATTAGE	➔ 1.2W
BATTERY	➔ 2.4V 1.7AH Ni-Cd
CHARGER.....	➔ Constant current
BATTERY PROTECTION	➔ Low voltage cut-off to prevent over discharge
MONITORING	➔ Red LED "ON" indicates charging Equipped with push test switch to simulate power failure
BACK UP DURATION	➔ 3 hours
RECHARGE TIME	➔ 16-24 hours
INPUT VOLTAGE	➔ 240V +/- 10% 50/60Hz
INPUT POWER	➔ 3W
WEIGHT	➔ 1.4kg
HOUSING	➔ Injection moulded / polycarbonate diffuser and housing. Vinyl stick-on signage.
MOUNTING	➔ Surface mount
DIMENSIONS (MM)	➔ 655mm (L) x 152mm (W) x 102mm (H)
INGRESS PROTECTION	➔ IP-65
OPERATING TEMPERATURE.....	➔ 0°C - 65°C
COMPLIANCE	➔ MS2687:2018 , MS619-2-22:2005 (IEC 60598-1:2020) , MS IEC 60598-1:2021

For further enquiries, please contact :

PNE SYSTEMS SDN. BHD.(263861 D)

No.3, Jalan SS26/13, Taman Mayang Jaya
47301, Petaling Jaya, Selangor Darul Ehsan.

Tel : (6)03-78037488 (Hunting)

Fax : (6)03-78038509

E-mail : sales@pnesys.com.my

Website : www.pnesys.com.my

Note : Due to continuous development and improvement, our company reserves the right to change specifications without notice.