



Self-Contained Emergency Luminaire

2 x 3.0 Power LED. Weatherproof fitting (IP 65).

TEL-30-LED (WP)

TEL-30-LED (WP)



Specifications

MODEL	➔	TEL-30-LED (WP)
MODE	➔	Non-maintained
LIGHT SOURCE	➔	2 x 3.0W High Power LED
LAMP WATTAGE	➔	2 x 3.0W
RATED LUMEN OUTPUT	➔	312 lm
BATTERY	➔	4 X 1.2V, 4.5AH Ni-cad
CHARGER.....	➔	Constant current
BATTERY PROTECTION	➔	Low voltage cut-off to prevent over discharge
MONITORING	➔	Red LED "ON" indicates charging Equipped with push test switch to simulate power failure
BACK UP DURATION	➔	3 hours
RECHARGE TIME	➔	16-24 hours
INPUT VOLTAGE	➔	240V +/- 10% 50Hz/60Hz
INPUT POWER	➔	2.8W
WEIGHT	➔	~1.6 Kg
HOUSING	➔	Injection moulded fire retarded ABS housing, IP-65 rated
MOUNTING	➔	Surface mount
DIMENSIONS (MM)	➔	82mm (L) x 198mm (W) x 240mm (H)
INGRESS PROTECTION	➔	IP-65
OPERATING TEMPERATURE	➔	0°C - 65°C
COMPLIANCE	➔	MS2687:2018 , MS619-2-22:2005 , MS IEC 60598-1:2021

For further enquiries, please contact :

PNE SYSTEMS SDN. BHD.(263861 D)

No.3, Jalan SS26/13, Taman Mayang Jaya
47301, Petaling Jaya, Selangor Darul Ehsan.

Tel : (6)03-78037488 (Hunting)

Fax : (6)03-78038509

E-mail : sales@pnesys.com.my

Website : www.pnesys.com.my

Note : Due to continuous development and improvement, our company reserves the right to change specifications without notice.



TEL 30 LED WP INSTALLATION DIAGRAM

